

# G-Blok®

G-Blok®, the paving surface that will provide a good, durable, load bearing and riding surface, requiring little maintenance.



# Product features

## G-Blok® precision saves money

- Fewer base layers are required because the precision-made interlocking G-Blok® forms an integral part of the structure, carrying and spreading the load.
- Little maintenance is required as the interlocking action of the G-Blok® spreads the load, reducing rutting in heavy traffic areas. The chamfered tap edges reduce chipping and assist in preserving the jointing sand.
- The paved surface is highly durable because of the strength and load-spreading abilities of the G-Blok®.
- There is less wastage and a neat finish with the unique full and half edge G-Blok®.

## G-Blok® versatility for good looks and peace of mind

- Exciting and interesting patterns can be created with the plain and coloured G-Blok® and the crazed edge Craz"E"® G-Blok®.
- The surface can be reinstated after lifting the G-Blok® to get to underground services.
- Both level and sloping surfaces can be covered, as the interlocking action of G-Blok® works on any slope.
- G-Blok® paving can be used in both heavy traffic and stacking areas and under most soil conditions because of its load-carrying and spreading abilities.
- Over 80% of G-Blok® can be recovered and re-used, even after many years in use.
- The paved area can be in use immediately on completion, as there are no wet trades.
- G-Blok® paving has a safe surface, particularly when wet, because of the textured, non-slip finish of the pavers.
- The Craz"E"® textured block offers an architectural alternative to industrial paving.

## G-Blok® applications


Heavy industrial areas, heavy parking areas, abnormally heavy industrial stacking areas, medium industrial working areas, parking areas and driveways, service areas and sloped embankments.

## Coverage

Approximately 40 blocks per m<sup>2</sup>.

## Estimating

Allowance must be made for laying tolerance and edge cutting.



## Dimensions

Length: 221.2mm  
Width: 110.8mm  
Thickness: 60 or 80mm.

